


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16H 1/34		A1	(11) International Publication Number: WO 00/66912
			(43) International Publication Date: 9 November 2000 (09.11.00)
(21) International Application Number: PCT/KR00/00395		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 26 April 2000 (26.04.00)		Published <i>With international search report.</i> <i>In English translation (filed in Korean).</i>	
(30) Priority Data: 1999/7601 U 30 April 1999 (30.04.99) KR			
(71) Applicant (for all designated States except US): KOREA INSTITUTE OF MACHINERY AND MATERIALS [KR/KR]; 171 Jang-dong, Yusong-gu, Taejon 305-343 (KR).			
(71)(72) Applicant and Inventor: CHOI, Byong, Chol [KR/KR]; 73-4 Sharim-dong, Changwon 641-241 (KR).			
(72) Inventor; and (75) Inventor/Applicant (for US only): KIM, Wan, Doo [KR/KR]; 205-1307 Mokryun Apt., Doonsan-dong, Seo-gu, Taejon 302-120 (KR).			
(74) Agents: PARK, Hee, Jin et al.; 401 Miele Haus Building, 607-10, Yoksam-dong, Kangnam-gu, Seoul 135-080 (KR).			

(54) Title: TRANSMITTING UNIT

(57) Abstract

A transmitting unit which uses bearings and the eccentric principle to reduce or increase the rotational speed. An eccentric portion is integrally formed with an input shaft, and a bearing is assembled along the outer periphery of the eccentric portion. The bearing is eccentrically moved when the input shaft is rotated. The bearing is surrounded by an integrally formed transmitting race, and a plurality of radial holes are formed in the transmitting race. The same plurality of transmitting rods are respectively inserted into the radial holes of the transmitting race. An integrally formed outer race surrounds the outer periphery of the transmitting race, and has a plurality of wave grooves on the inner periphery thereof. The same plurality of balls are respectively provided between the transmitting rods and the wave grooves of the outer race, while the balls roll on the wave grooves. According to the transmitting unit, the strength of the unit can increase as the unit can be minimized, while the noise and the vibration of the unit can decrease.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TRANSMITTING UNIT

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a transmitting unit, and more particularly to a transmitting unit using bearings and the eccentric principle to reduce or increase the rotational speed.

2. Description of the Prior Art

10 Conventionally, a transmitting unit reducing the rotational speed, which has been industrially used, reduces or increases the rotational speed of the input shaft mainly by disposing gears. The transmitting unit mainly uses worm gears or epicyclical trains, and examples of the transmitting unit are disclosed in Japanese Patent Laid-open No. Sho 60-91043 and Japanese Patent Laid-open No. Sho 63-214542 for further details.

15 However, since the aforementioned transmitting unit uses relative movement of meshed gears, much power is lost and much noise and vibration is generated. Beyond that, the transmitting unit is mainly used for heavy load. Furthermore, the structure of the transmitting unit is so complicated that it is hard to install the unit, and an output shaft is reversibly rotated when an input shaft is rotated.

20 In order to settle the aforementioned problems, U.S. Patent No. 4,736,654 allowed to Zhu S. Ren and entitled "transmitting unit" discloses a transmitting unit reducing speed that uses bearings.

According to the transmitting unit of Ren, an eccentric sleeve and bearings are rotated to push transmitting rods, when an input shaft is rotated. In addition, rolling members that are linearly moved in a radial direction on the outer sides of the transmitting rods are moved along the waves of an outer race.

- 5 By the aforementioned operation, the rotational speed of an output shaft mounted to the transmitting race is reduced, and the output shaft is rotated in the same rotational direction as that of the input shaft.

However, the structure of the transmitting unit has a disadvantage in that it is complicated and many parts are required to assemble the transmitting unit.

- 10 Furthermore, the transmitting unit cannot be easily manufactured. Namely, the transmitting unit is rather an ideal unit.

SUMMARY OF THE INVENTION

- The present invention has been made to solve the aforementioned problem, and
15 accordingly it is an object of the present invention to provide a transmitting unit that has an integrally formed transmitting race, an integrally formed outer race, and an input shaft in which an eccentric portion is integrally formed therewith, without using a separate eccentric sleeve so as to increase the strength of the unit and minimize the unit.

- 20 It is another object of the present invention to provide a transmitting unit that is precisely maintained and decreases the noise and the vibration thereof during the operation of the unit.

In order to achieve the aforementioned objects of the present invention, the present invention provides a transmitting unit comprising an input shaft driven by a driving device; a sleeve driven together with the input shaft when the input shaft is driven and having a first concentric portion, a second concentric portion, and an eccentric portion; a first bearing assembled along the outer periphery of the first concentric portion; a second bearing assembled along the outer periphery of the second concentric portion; a third bearing assembled along the outer periphery of the eccentric portion and strangely enough moving when the input shaft is driven; an integrally formed transmitting race having a first flange surrounding the outer periphery of the first bearing, a second flange surrounding the outer periphery of the second bearing, and a third flange surrounding the outer periphery of the third bearing and integrally formed with the first and second flanges, the third flange having a plurality of radial holes spaced apart at a predetermined distance; the same plurality of transmitting rods respectively inserted into the radial holes of the third flange of the transmitting race; an integrally formed outer race located out of the transmitting race and having a plurality of wave grooves on the inner periphery thereof; and the same plurality of balls respectively provided between the transmitting rods and the wave grooves of the outer race in order to roll on the wave grooves.

According to one aspect of the present invention, the sleeve is integrally formed with the input shaft.

According to the other aspect of the present invention, the first to third bearings are ball bearings, and the transmitting rod has a circular cross-section.

Preferably, a semi-spherical recess is formed on one side of each transmitting rod so that the corresponding ball is positioned in the recess.

Preferably, the same plurality of rollers are respectively provided between the third bearing and the transmitting rods, and a groove is formed on one side of each
5 transmitting rod so that the corresponding roller is positioned in the groove.

Preferably, a pair of fourth bearings is provided between the outer race and the transmitting race, and the fourth bearings are respectively assembled around the first and second flanges of the transmitting race.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and advantages of the present invention will get readily apparent with reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is an exploded perspective view showing a transmitting unit according to a
15 preferred embodiment of the present invention;

FIG. 2 is a cross-sectional view showing the transmitting unit according to the preferred embodiment of the present invention; and

FIG. 3 is a cross-sectional view that is taken along the line A-A of FIG. 2.

20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, preferred embodiments of the present invention will be explained in detail with reference to the attached drawings.

FIG. 1 is an exploded perspective view showing a transmitting unit according to a preferred embodiment of the present invention. FIG. 2 is a cross-sectional view for showing the transmitting unit according to the preferred embodiment of the present invention, and FIG. 3 is a cross-sectional view that is taken along the line A-A of FIG. 2.

5 Referring to FIGs. 1 and 2, a transmitting unit according to a preferred embodiment of the present invention includes an input shaft 110 driven by a driving device 100, a transmitting race 130, and an outer race 150.

The input shaft 110 has a conventional key groove 112, and as shown in FIG. 2, the driving device 100 is assembled to the input shaft 110 by a key (not shown).

10 A sleeve 120 is integrally formed with the input shaft 110, and has a first concentric portion 122, a second concentric portion 124, and an eccentric portion 126. As shown in FIG. 1, the first and second concentric portions 122 and 124 and the eccentric portion 126 are integrally formed.

15 If the sleeve 120 is integrally formed with the input shaft 110 as in the present invention, a separate sleeve is not needed. Thus, the number of parts of the unit is decreased and the unit can be minimized.

20 A first bearing 142 is assembled along the outer periphery of the first concentric portion 122, and a second bearing 144 is assembled along the outer periphery of the second concentric portion 124. And, a third bearing 146 is assembled along the outer periphery of the eccentric portion.

The first and second bearings 142 and 144 support the third bearing 146, and reduce the frictional speed when the transmitting race 130. The third bearing 146 is

eccentrically moved when the input shaft 100 is driven.

According to the present invention, ball bearings are used as the first to third bearings 142, 144, and 146 in a transmitting unit for light load, and ball bearing are used as the first and second bearings 142 and 144 and a roller bearing is used as the
5 third bearing 146 in a transmitting unit for heavy load. But, roller bearings may be used as the first to third bearings 142, 144, and 146.

The integrally formed transmitting race 130 is installed on the outer peripheries of the first and second bearings 142, 144, and 146. The transmitting race 130 has a first flange 132, a second flange 134, and a third flange 136. According to an aspect of the
10 present invention, the transmitting race 130 is integrally formed.

The first flange 132 surrounds the outer periphery of the first bearing 142, and the second flange 134 surrounds the outer periphery of the second bearing 144. The third flange 136 surrounds the third bearing, and is integrally formed with the first and second flanges 132 and 134. As shown in FIG. 1, the third flange 136 has a plurality of
15 radial holes that are spaced apart by a predetermined distance.

Transmitting rods 140 are inserted into the radial holes 137 of the third flange 136 of the transmitting race 130, respectively. The transmitting rods 140 are movable in a radial direction in the radial holes 137, and have a circular cross-section.

As shown in FIG. 1, a plurality of engagement holes 135 are formed on the front
20 surface of the second flange 134. An output shaft (not shown) is assembled to the engagement holes 135 by a flange-type engaging appliance (not shown).

The outer race 150 surrounds the outer periphery of the transmitting race 130,

and has a plurality of wave grooves 152 on the inner periphery thereof, as shown in FIG.

3.

According to the preferred embodiment of the present invention, the wave grooves 152 are disposed in a row, but may be disposed in a pair of rows.

5 Balls 160 are provided between the transmitting rods 140 and the wave grooves 152 of the outer race 150 and roll on the wave groove 152. A semi-spherical recess 143 is formed on one side of each transmitting rod 140 so that the corresponding ball 160 is positioned in the recess 143.

10 According to the present invention, the balls 160 roll between the transmitting rods 140 and the outer race 150, which reduces the frictional forces, compared to the case rollers roll between them. On top of that, the balls can endure axial loads.

15 The wave groove 152 is designed such that the balls 160 make surface contact with the wave grooves 152 when rolling on the wave grooves 152. Therefore, the contact stress in the balls 160 during the operation of the unit is given out, and thus the lives of the balls are prolonged.

Rollers 147 are provided between the third bearing 146 and the transmitting rods 140 respectively, a groove 145 is formed on one side of each transmitting rod 140 so that the corresponding roller 147 is positioned in the groove 145.

20 The outer race 150 is integrally formed, and a pair of fourth bearings 170 are provided between the transmitting race 130 and the outer race 150. As shown in FIG. 2, the fourth bearings 170 are assembled around the first and second flanges 132 and 134 of the transmitting race 130. In the preferred embodiment of the present invention,

ball bearings are used as the fourth bearings 170.

The fourth bearings 170 support the loads of the transmitting race 130 during the transmission on both sides of the transmitting race 130, and thus minimize the deformation of the input shaft 110. Therefore, the precision of the assembly maintained
5 even during the operation of the unit, and the vibration and the noise are minimized.

Hereinafter, the operation of the above-mentioned transmitting unit will be explained with reference to FIGs. 2 and 3.

Firstly, after the input shaft 110 of the transmitting unit according to the present invention is assembled to the driving device 100, the driving force is transferred to the
10 input shaft 110 from the driving device 100. When the driving force rotates the input shaft 110, the rotational force is transferred to the first to third bearings 142, 144, and 146.

When the input shaft 110 is rotated, the eccentric portion 126 of the sleeve 120 integrally formed with the input shaft 110 is rotated, moving between a and b of FIG. 3.
15 Therefore, the driving force of the input shaft 110 and the rotational force of the eccentric portion 126 are transferred to the third bearing 146.

As mentioned above, the third bearing 146 is eccentrically rotated, and thus the transmitting rods 146 are reciprocated in the holes 137.

The ball 160 provided on one side of each transmitting rod 140 rolls along the
20 wave groove 152 of the outer race 150, and simultaneously the transmitting rod 140 rotates the transmitting race 130.

Then, since the transmitting rods are symmetrical with reference to the central

point of the input shaft 110, as shown in FIG. 3, when the ball 160 of the transmitting rod 140 which is located on the upper side of the unit is located at a highest point 152A of the wave groove 152, the ball 160 of the transmitting rod 140 which is located on the lower side of the unit is located at a lowest point 152B of the wave groove 152.

5 According to the operation of the unit, if the input shaft 110 is rotated, the output shaft (not shown) assembled to the transmitting race 130 is rotated at a reduced rotational speed.

 As stated above, preferred embodiments of the present invention are shown and described. Although the preferred embodiments of the present invention have been
10 described, it is clearly understood that the present invention should not be limited to these preferred embodiments but a variety of changes and modifications can be made by one skilled in the art within the spirit and scope of the present invention as hereinafter claimed.

15 INDUSTRIAL APPLICABILITY

 As described above, the transmitting unit based on the present invention has an integrally formed transmitting race, an integrally formed outer race, and an input shaft in which an eccentric portion is integrally formed, without using a separate eccentric sleeve, and thereby the causes of the assembly tolerances are basically settled.
20 Therefore, since the unit is precisely maintained, the operation of low vibration and low noise can be easily achieved. Furthermore, according to the unit of the present invention, the life of the unit becomes prolonged, and the strength of the unit is

maintained. Since the number of parts becomes remarkably reduced, the manufacturing cost of the unit could be reduced.

What is claimed is:

1. A transmitting unit comprising:

an input shaft driven by a driving device;

a sleeve driven together with the input shaft when the input shaft is driven and

5 having a first concentric portion, a second concentric portion, and an eccentric portion;

a first bearing assembled along the outer periphery of the first concentric portion;

a second bearing assembled along the outer periphery of the second concentric
portion;

a third bearing assembled along the outer periphery of the eccentric portion and
10 eccentrically moving when the input shaft is driven;

an integrally formed transmitting race having a first flange surrounding the outer
periphery of the first bearing, a second flange surrounding the outer periphery of the
second bearing, and a third flange surrounding the outer periphery of the third bearing
and integrally formed with the first and second flanges, the third flange having a
15 plurality of radial holes spaced apart by a predetermined distance;

the same plurality of transmitting rods respectively inserted into the radial holes
of the third flange of the transmitting race;

an integrally formed outer race located outside the transmitting race and having
a plurality of wave grooves on the inner periphery thereof; and

20 the same plurality of balls respectively provided between the transmitting rods
and the wave grooves of the outer race so as to roll on the wave grooves.

2. A transmitting unit according to claim 1, wherein the sleeve is integrally formed with the input shaft.

3. A transmitting unit according to claim 1, wherein the first to third bearings
5 are ball bearings.

4. A transmitting unit according to claim 1, wherein the first and second bearings are ball bearings, and the third bearing is a roller bearing.

10 5. A transmitting unit according to claim 1, wherein the transmitting rod has a circular cross-section.

6. A transmitting unit according to claim 1, wherein a semi-spherical recess is formed on one side of each transmitting rod so that the corresponding ball is
15 positioned in the recess.

7. A transmitting unit according to claim 1, wherein the same plurality of rollers are respectively provided between the third bearing and the transmitting rods, and a groove is formed on one side of each transmitting rod so that the corresponding
20 roller is positioned in the groove.

8. A transmitting unit according to claim 1, wherein a pair of fourth bearings

are provided between the outer race and the transmitting race, whereas the fourth bearings are respectively assembled around the first and second flanges of the transmitting race.

5 9. A transmitting unit according to claim 8, wherein the fourth bearings are ball bearings.

 10. A transmitting unit according to claim 1, wherein the wave grooves are disposed in a row.


10

 11. A transmitting unit according to claim 1, wherein the wave grooves are disposed in a pair of rows.

 12. A transmitting unit according to claim 1, wherein the balls make surface
15 contact with the wave groove while rolling on the wave grooves.


1/3

FIG. 1




2/3

FIG. 2



3/3

FIG. 3



INTERNATIONAL SEARCH REPORT

international application No.
PCT/KR00/00395**A. CLASSIFICATION OF SUBJECT MATTER****IPC7 F16H 1/34**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16H 1/32, 1/34

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

KR, JP : IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,736,654 A (Hubi Institute of Machinery) 12 April 1988 See column 1 line 65 - column 2 line 33; Figures 1-4	1-3, 10-11
Y	JP 7-243,486 A (Sumitomo Heavy Ind. Ltd.) 19 September 1995 See the whole document	1-3, 10-11
A	JP 6-241,283 A (Sumitomo Heavy Ind. Ltd.) 30 August 1994 See the whole document	1-12
A	EP 408,314 B (Zheng Yue Lian) 16 January 1991 See the whole document	1-12
A	JP 4-202,296 A (Kiyofuji Yoshio) 8 February 1994 See the whole document	1-12

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

14 AUGUST 2000 (14.08.2000)

Date of mailing of the international search report

21 AUGUST 2000 (21.08.2000)

Name and mailing address of the ISA/KR

Korean Industrial Property Office
Government Complex-Taejon, Dunsan-dong, So-ku, Taejon
Metropolitan City 302-701, Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

LEE, Hak Soo

Telephone No. 82-42-481-5454



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR00/00395

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4,736,654 A	12-04-88	EP 196650 A1 CN 85200923 U AT 36593 E JP 61294253 A2	08-10-86 12-02-86 15-09-88 25-12-86
JP 7-243,486 A	19-09-95	FR 2717239 A1 US 5707310 A	15-09-95 13-01-98
JP 6-241,283 A	30-08-94	None	
EP 408,314 B	16-01-1991	AT 118865 E AU 591290 A CN 1048744 A EP 408314 A	15-03-95 17-01-98 23-01-91 03-08-93
JP 4-202,296 A	08-02-94	None	